



36 x 26 SCREEN500 SPECIFICATIONS

SCREEN500

Style #	19295-S5
FIBER CONTENT/FINISH	Vinyl Coated Polyester with Abrasion Resistance
CONSTRUCTION	36 x 26
DENIER	500
WEIGHT (ASTM D-3776)	17.8 oz/yd ²
SHADE FACTOR	95%
THICKNESS	0.037 in
TENSILE STRENGTH (ASTM D-5035, Strip Method)	Warp: 314.9 lbf Fill: 224.1 lbf
ELONGATION (ASTM D-5035, Strip Method)	Warp: 32.3% Fill: 24.9%
TRAPEZOIDAL TEAR STRENGTH (ASTM D-4533)	Warp: 87.6 lbf Fill: 57.4 lbf
FLAMMABILITY RATING	CA Title 19 & NFPA 701
WEATHERABILITY (G154)	1,200 Hours
AVAILABLE WIDTH(S)*	126"
AVAILABLE COLOR(S)*	White, Black, Tan, Grey, Tan/White, Brown/Black, Grey/Black
<small>Technical data provided by producing mill for first quality run of equivalent product. Results will vary with Seconds. Values are subject to updating at the sole discretion of Acadian Inc. Buyer is responsible for verifying the suitability of product for a particular application. In no event will Acadian Inc.'s liability for any sale exceed the purchase value of the product as invoiced for that sale. Acadian, Inc will never be liable for loss of profit, special, indirect, or consequential damages.</small>	

*Call for currently available widths and colors
Additional options may be available*