



**22 x 13.5 SCREENMAX SPECIFICATIONS**

**SECONDS**

<b>Style #</b>	<b>19291-SM</b>
<b>FIBER CONTENT/FINISH</b>	Vinyl Coated Polyester with Abrasion Resistance
<b>CONSTRUCTION</b>	22 x 13.5
<b>DENIER</b>	1500 x 2000
<b>WEIGHT</b> (ASTM D-3776)	19.52 oz/yd <sup>2</sup>
<b>SHADE FACTOR</b>	91%
<b>TENSILE STRENGTH</b> (ASTM D-5035, Strip Method)	Warp: 416.7 lbf Fill: 251.4 lbf
<b>ELONGATION</b> (ASTM D-5035, Strip Method)	Warp: 42.8% Fill: 12.3%
<b>TRAPEZOIDAL TEAR STRENGTH</b> (ASTM D-4533)	Warp: 181.6 lbf Fill: 285 lbf
<b>PUNCTURE RESISTANCE</b> (ASTM D-4833)	364 lbf
<b>FLAMMABILITY RATING</b>	CA Title 19 & NFPA 701
<b>WEATHERABILITY</b> (G154)	1,200 Hours
<b>AVAILABLE WIDTH(S)*</b>	126".
<b>AVAILABLE COLOR(S)*</b>	White, White/Tan, Black/Tan, Black
<small>Technical data provided by producing mill for first quality run of equivalent product. Results will vary with Seconds. Values are subject to updating at the sole discretion of Acadian Inc. Buyer is responsible for verifying the suitability of product for a particular application. In no event will Acadian Inc.'s liability for any sale exceed the purchase value of the product as invoiced for that sale. Acadian, Inc will never be liable for loss of profit, special, indirect, or consequential damages.</small>	

\*Call for currently available widths and colors  
Additional options may be available\*.